



NORTH SAILS

Swan 45 Quick Tune Guide, Updated February 2010

Base Settings used in 12 knots

Headstay Arc Measurement	124 cm
Mast Butt	4 cm from bulkhead
Cap Shroud Tension	NA
D1 Tension	NA
D2 Tension	NA
J Dimension	Fixed at Class max.
Pre-Bend	4cm

There are no Loos Gauges for the Swan 45 rig because it's too big. Mast is set-up straight sideways at 3900 Jack Pressure. All windpseed tuning adjustments are based on the number of 360 degree turns on or off.

	TWS	ARC	Headstay	Cap	D1	D2	Headsail	Spinnaker	Jack
	5		-7	-3	-4	-2	Light	1A	2300
	6		-7	-3	-4	-2	Light	1A	2300
	8		-4	-3	-3	0	Light	1A	3000
	10		-2	-2	-2	0	Light	A2/A1	3500
Base Settings	12	1.24	0	0	0	0	Medium	S2/A2	3900
	14		2	2	1	1	Medium	S2/A2	4500
	16		6	2	2	2	Medium	S2	5000
	18		8	2	2	2	Heavy	S4	5500
	20		12	3	3	2	Heavy	S4	5800
	22		15	3	3	2	Heavy	S4	6000
	24		15	3	3	2	#4	S4	6000
	27		15	3	3	2	#4	S4	6000